



Product Specifications

FF105



Fuel, Spin-On

Fleetguard® FF105 fuel filter cartridge reduces contamination, trapping dirt particles and preventing them from reaching the moving parts in your engine supporting longer service intervals.

[View product on Fleetguard.com](#)

Specifications

Largest OD	3.69 inch	Length	5.41 inch
Gasket Inside Diameter	2.46 inch	Gasket OD	2.83 inch
Efficiency Test Std	SAE J905	Standpipe	No
Hydrostatic Burst Minimum	1380 kPa	Primary Particle Efficiency	17.3 micron (c) @ 96%
Rated Flow	348 L/min	Test Specification	SAE J905

Product Comments

Extended Life Version of FF104 w/o drain For Synthetic Media Version, use FF5332.

Related Parts

Upgrade Of FF104

Uses Service Part	154711S	255622S	3301519S
Filter Used With	3911894S 3930618S	142784S	212013S
Is A Shorter Version Of	FF213		
For Upgrade, Use	FF5332	FS1212	
Uses Service Gasket	3301519		

This publication and all information contained or referenced in it (hereinafter "Publication") are provided as a convenience to Cummins Filtration customers "as is" without any warranties, express or implied, including warranties of merchantability, fitness for a particular purpose, or non-infringement of intellectual property. Cummins Filtration does not warrant the accuracy nor completeness of the Publication; may make changes to the Publication at any time without notice; and makes no commitment to update the Publication.

The Publication may refer to products, programs, or services that are not available in your country or local area. Consult Cummins Filtration directly for information regarding the products, programs, and services that may be available to you. Applicable law may not allow the exclusion of implied warranties, so the above exclusion may not apply to you. © 2024 Cummins Filtration Inc. All Rights Reserved