



Product Specifications

FF5135



Fuel, Spin-On

Fleetguard® FF5135 premium spin-on fuel filter delivers superior performance using proven media technology, removing harmful contaminants. Fleetguard fuel filters ensure optimal fuel system protection to meet or exceed OEM specifications.

[View product on Fleetguard.com](https://www.fleetguard.com)

Specifications

Thread Size	M16 X 1.5-6H INT	Gasket OD	2.76 inch
Gasket Inside Diameter	2.46 inch	Largest OD	3.03 inch
Length	6.14 inch	Standpipe	No
Efficiency Test Std	ISO 19438	Hydrostatic Burst Minimum	217.49999999999997 psi
Primary Particle Efficiency	17 micron (c) @ 98.7%	Rated Flow	2.5 L/min

Product Comments

Product availability is limited to certain regions. Please contact your local representative to verify if it is available in your region.

Related Parts

For Stratapore Version, Use	FS19599
For European Version, Use	FF214
Replaces	FF5060
Is Metal Version Of	FF42006

This publication and all information contained or referenced in it (hereinafter "Publication") are provided as a convenience to Cummins Filtration customers "as is" without any warranties, express or implied, including warranties of merchantability, fitness for a particular purpose, or non-infringement of intellectual property. Cummins Filtration does not warrant the accuracy nor completeness of the Publication; may make changes to the Publication at any time without notice; and makes no commitment to update the Publication.

The Publication may refer to products, programs, or services that are not available in your country or local area. Consult Cummins Filtration directly for information regarding the products, programs, and services that may be available to you. Applicable law may not allow the exclusion of implied warranties, so the above exclusion may not apply to you. © 2024 Cummins Filtration Inc. All Rights Reserved