



# Product Specifications

FF5633



## Fuel, Spin-On

Fleetguard® FF5633 spin-on fuel filter delivers superior performance using proven media technology, removing harmful contaminants. Fleetguard fuel filters ensure optimal fuel system protection to meet or exceed OEM specifications.

[View product on Fleetguard.com](#)

## Specifications

Efficiency Test Std	ISO 19438	Hydrostatic Burst Minimum	434.99999999999994 psi
Rated Flow	8.5 L/min	Largest OD	4.33 inch
Length	10.2 in	Gasket OD	4.02 inch
Gasket Inside Diameter	3.71 inch		

This publication and all information contained or referenced in it (hereinafter "Publication") are provided asa convenience to Cummins Filtration customers "as is" without any warranties, express or implied, including warranties of merchantability, fitness for a particular purpose, or non-infringement of intellectual property.Cummins Filtration does not warrant the accuracy nor completeness of the Publication; may make changes to the Publication at any time without notice; and makes no commitment to update the Publication.

The Publication may refer to products, programs, or services that are not available in your country or local area. Consult Cummins Filtration directly for information regarding the products, programs, and services that may be available to you. Applicable law may not allow the exclusion of implied warranties, so the above exclusion may not apply to you. © 2024 Cummins Filtration Inc. All Rights Reserved