



# Product Specifications

## FS1280



### Fuel/Water Sep Spin-On

Fleetguard® FS1280 premium fuel water separator spin-on works to remove water and other particulates and ensures clean fuel is delivered to your engine.

[View product on Fleetguard.com](http://Fleetguard.com)

## Specifications

Thread Size	13/16-18 UNS-2B	Largest OD	3.69 inch
Length	6.49 inch	Gasket Inside Diameter	2.46 inch
Gasket OD	2.83 inch	Standpipe	NO
EMULSIFIED WATER SEPARATION	90 %	Hydrostatic Burst Minimum	300.15 psi
Test Specification	SAE J905		

## Product Comments

Not suitable for Marine applications

## Related Parts

<b>Replaces</b>	FF5038
<b>Separator Version Of</b>	FF5285
<b>Uses Service Gasket</b>	3311920

This publication and all information contained or referenced in it (hereinafter "Publication") are provided as a convenience to Cummins Filtration customers "as is" without any warranties, express or implied, including warranties of merchantability, fitness for a particular purpose, or non-infringement of intellectual property. Cummins Filtration does not warrant the accuracy nor completeness of the Publication; may make changes to the Publication at any time without notice; and makes no commitment to update the Publication.

The Publication may refer to products, programs, or services that are not available in your country or local area. Consult Cummins Filtration directly for information regarding the products, programs, and services that may be available to you. Applicable law may not allow the exclusion of implied warranties, so the above exclusion may not apply to you. © 2024 Cummins Filtration Inc. All Rights Reserved