




Product Specifications

HF7076



Hydraulic, Cartridge

Fleetguard® HF7076 hydraulic cartridge filter with synthetic media is designed to help keep your precision hydraulic systems running as intended, providing a solution for various applications. This filter meets or exceeds the equipment OEM quality and performance and is the first aftermarket replacement available on the market today, bringing your operation top-quality performance and an overall unbeatable total cost of ownership.

[View product on Fleetguard.com](#)

Specifications

Length	16.86 inch	Largest OD	3.12 inch
Efficiency Test Std	ISO 4572	Particle Size at Beta 200	6.5 Micron
Particle Size at Beta 75	5.1 Micron	Rated Flow	170 L/m
Element Collapse/Burst, Min	1034 kPa	Test Specification	ISO 4572

Related Parts

For Upgrade, Use HF30584

This publication and all information contained or referenced in it (hereinafter "Publication") are provided as a convenience to Cummins Filtration customers "as is" without any warranties, express or implied, including warranties of merchantability, fitness for a particular purpose, or non-infringement of intellectual property. Cummins Filtration does not warrant the accuracy nor completeness of the Publication; may make changes to the Publication at any time without notice; and makes no commitment to update the Publication.

The Publication may refer to products, programs, or services that are not available in your country or local area. Consult Cummins Filtration directly for information regarding the products, programs, and services that may be available to you. Applicable law may not allow the exclusion of implied warranties, so the above exclusion may not apply to you. © 2024 Cummins Filtration Inc. All Rights Reserved