



# Product Specifications

## LF3327



### Lube, Cartridge

Fleetguard® LF3327 premium cartridge oil filter is environmentally friendly and features technology advances to achieve the high flow rates required by today's modern engine designs.

[View product on Fleetguard.com](https://www.fleetguard.com)

### Specifications

Length	10.57 inch	Largest End ID	2.20 inch
Largest OD	4.74 inch	Gasket Inside Diameter	2.52 inch
Efficiency Test Std	ISO 4548-12	Pressure Valve	No
Element Collapse/Burst, Min	400 kPa	Primary Particle Efficiency	0.987
Rated Flow	110 L/m	Test Specification	ISO 4548-12

### Related Parts

<b>Replaces</b>	LF4053	LF4144
<b>Uses Service Gasket</b>	3324572	

This publication and all information contained or referenced in it (hereinafter "Publication") are provided as a convenience to Cummins Filtration customers "as is" without any warranties, express or implied, including warranties of merchantability, fitness for a particular purpose, or non-infringement of intellectual property. Cummins Filtration does not warrant the accuracy nor

completeness of the Publication; may make changes to the Publication at any time without notice; and makes no commitment to update the Publication.

The Publication may refer to products, programs, or services that are not available in your country or local area. Consult Cummins Filtration directly for information regarding the products, programs, and services that may be available to you. Applicable law may not allow the exclusion of implied warranties, so the above exclusion may not apply to you. © 2024 Cummins Filtration Inc. All Rights Reserved