



# Product Specifications

## LF3957



### Lube

Fleetguard® LF3957 spin-on lube filter meets or exceeds OE performance requirements and the new challenges of modern engine technology.

[View product on Fleetguard.com](https://www.fleetguard.com)

### Specifications

Thread Size	1 1/2-16 UNS-2B	Length	12.20 inch
Largest OD	5.45 inch	Gasket Inside Diameter	3.43 inch
Gasket OD	4.26 inch	Media Type	Cellulose
Pressure Valve	Yes	Hydrostatic Burst Minimum	202.9971 psi
Rated Flow	10.599 L/m		

This publication and all information contained or referenced in it (hereinafter "Publication") are provided as a convenience to Cummins Filtration customers "as is" without any warranties, express or implied, including warranties of merchantability, fitness for a particular purpose, or non-infringement of intellectual property. Cummins Filtration does not warrant the accuracy nor completeness of the Publication; may make changes to the Publication at any time without notice; and makes no commitment to update the Publication.

The Publication may refer to products, programs, or services that are not available in your country or local area. Consult Cummins Filtration directly for information regarding the products,

programs, and services that may be available to you. Applicable law may not allow the exclusion of implied warranties, so the above exclusion may not apply to you. © 2024 Cummins Filtration Inc. All Rights Reserved